

SAFETY DATA SHEET**030YE11 MUNSELL YELLOW PVC CC**

Version Number 1.15
Revision Date 09/07/2023

Page 1 of 19
Print Date 09/08/2023

SAFETY DATA SHEET**030YE11 MUNSELL YELLOW PVC CC****Section 1. Identification**

GHS product identifier : 030YE11 MUNSELL YELLOW PVC CC
Chemical name : Mixture
CAS number : Mixture
Other means of identification : CC00012577
Product type : solid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **AVIENT CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012
 1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. Some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : EYE IRRITATION - Category 2B
 CARCINOGENICITY - Category 1A

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 2 of 19
 Print Date 09/08/2023

Signal word : Danger
Hazard statements : Causes eye irritation.
 May cause cancer.

Precautionary statements

Prevention : Not applicable.
 : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Wash thoroughly after handling.

Response : IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage : Store locked up.
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : None known.
Hazards not otherwise classified : None known.
 Not available.

Section 3. Composition/information on ingredients
--

Substance/mixture : Mixture
Chemical name : Mixture
Other means of identification : CC00012577

CAS number/other identifiers

Ingredient name	%	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 10 - <= 25	68515-48-0
Chrome yellow (Lead chromate pigment)	>= 10 - <= 25	1344-37-2
Titanium dioxide	>= 5 - <= 10	13463-67-7
Quartz	> 0 - <= 0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 3 of 19
 Print Date 09/08/2023

reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
Revision Date 09/07/2023

Page 4 of 19
Print Date 09/08/2023

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO₂.
- Unsuitable extinguishing media** : None known.
- Specific hazards arising from the chemical** : No specific fire or explosion hazard.
- Hazardous thermal decomposition products** : May emit Hydrogen Chloride (HCl).
Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
halogenated compounds
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
Revision Date 09/07/2023

Page 5 of 19
Print Date 09/08/2023

- Special protective equipment for fire-fighters** :
- personal risk or without suitable training.
 - Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** :
- No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** :
- If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** :
- Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** :
- Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** :
- Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** :
- Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 6 of 19
 Print Date 09/08/2023

- until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
 - Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	None.
Chrome yellow (Lead chromate pigment)	<p>ACGIH TLV (2018-03-20) TWA 0.0002 mg/m³ (as Cr) Form: Inhalable fraction STEL 0.0005 mg/m³ (as Cr) Form: Inhalable fraction NIOSH REL (2010-09-01) TWA 0.0002 mg/m³ OSHA PEL 1989 (1989-03-01) CEIL 0.1 mg/m³ (as CrO₃) OSHA PEL 1989 (1989-03-01) TWA 0.05 mg/m³ (calculated as Pb) OSHA PEL (2006-11-27) TWA 0.005 mg/m³ (as Cr) OSHA PEL (1993-06-30) TWA 0.05 mg/m³ (calculated as Pb)</p>

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 7 of 19
 Print Date 09/08/2023

	<p>OSHA PEL Z2 (2006-11-27) CEIL 0.001 mg/m³</p>
Titanium dioxide	<p>OSHA PEL 1989 (1989-03-01) TWA 10 mg/m³ Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m³ Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m³ Form: respirable fraction, nanoscale particles TWA 2.5 mg/m³ Form: respirable fraction, finescale particles</p>
Quartz	<p>OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m³ (Calculated as Quartz) Form: Respirable dust OSHA PEL Z3 (1997-09-03) TWA 250 MPPCF / (%SiO₂+5) Form: Respirable TWA 10 MG /M3 / (%SiO₂+2) Form: Respirable OSHA PEL Z3 (1997-09-03) TWA 30 MG /M3 / (%SiO₂+2) Form: Total dust NIOSH REL (1994-06-01) TWA 0.05 mg/m³ Form: Respirable dust ACGIH TLV (2005-12-09) TWA 0.025 mg/m³ Form: Respirable fraction OSHA PEL (2016-06-23) TWA 0.05 mg/m³ Form: Respirable dust</p>

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SAFETY DATA SHEET**030YE11 MUNSELL YELLOW PVC CC**

Version Number 1.15
Revision Date 09/07/2023

Page 8 of 19
Print Date 09/08/2023

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties
--

Appearance

Physical state : solid [Pellets.]
Color : YELLOW
Odor : Not available.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : Not available.
Flash point : Not applicable.

Burning time : Not available.
Burning rate : Not available.
Evaporation rate : Not available.

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
Revision Date 09/07/2023

Page 9 of 19
Print Date 09/08/2023

Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	:	Lower: Not applicable. Upper: Not applicable.
Vapor pressure	:	Not available.
Vapor density	:	Not applicable.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available. Kinematic: Not applicable.

Aerosol product

Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition - Deflagration density	:	Not available.
Flame height	:	Not available.
Flame duration	:	Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 10 of 19
 Print Date 09/08/2023

Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). Do not use this pigment in polymers at temperatures over 200°C (392°F). Decomposition of diarylide pigments in polymers at temperatures over 200°C (392°F) may produce trace amounts of monoazo dyes, which in turn can decompose to produce aromatic amines. The amount and type of degradation products formed depend on the dwell time, formulation and processing conditions as well as temperature. As conditions become more severe, as when temperatures move into the 240-300°C (464-572°F) range, trace quantities of 3,3'-dichlorobenzidine can be generated. 3,3'-dichlorobenzidine is classified as a suspect carcinogen by NTP and IARC, is classified as Acute Toxicity category 4 and Carcinogen Category 1B according to 1272/2008EC (CLP), and is regulated by OSHA as a suspect carcinogen. In order to avoid the generation of and exposure to 3,3'-dichlorobenzidine, do not use diarylide pigments in polymers when temperatures exceed 200°C (392°F). Handle with care. Organic dusts have the potential to be explosive with static spark or flame initiation.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich				
	LD50 Oral	Rat	10,000 mg/kg	-
Titanium oxide (TiO2)				
	LC50 Inhalation Dusts and mists	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Eyes - Mild irritant	Rabbit	-		-

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 11 of 19
 Print Date 09/08/2023

Respiratory : Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary

: Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary

: Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
C.I. Pigment Yellow 34	+	12A	Known to be a human carcinogen.Reasonably anticipated to be a human carcinogen.
Titanium oxide (TiO2)	-	2B	-
Quartz (SiO2)	-	1	Known to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Quartz (SiO2)	Category 1	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 12 of 19
 Print Date 09/08/2023

- Eye contact** : Causes eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following: irritation, watering, redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

- Conclusion/Summary** : Mixture. Not fully tested.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards. No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 13 of 19
 Print Date 09/08/2023

030YE11 MUNSELL YELLOW PVC CC	271532.8 mg/kg	N/A	N/A	N/A	N/A
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10000 mg/kg	N/A	N/A	N/A	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l

Other information : This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fundulus heteroclitus	96 h
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 h
	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	8.8	3.00	low
C.I. Pigment Yellow 34	-	3,600.00	high

Mobility in soil

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 14 of 19
 Print Date 09/08/2023

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA : Consult mode specific transport rules

International Water IMO/IMDG : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : **United States - TSCA 12(b) - Chemical export notification:** The following components are listed: **Chrome yellow (Lead chromate**



SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 15 of 19
 Print Date 09/08/2023

pigment)

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

United States - TSCA 4(a) - ITC Priority list: Not listed

United States - TSCA 4(a) - Proposed test rules: Not listed

United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not listed

United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

United States - TSCA 6 - Final risk management: Listed **Chrome yellow (Lead chromate pigment)**

United States - TSCA 6 - Proposed risk management: Not listed

United States - TSCA 8(a) - Chemical risk rules: Not listed

United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed

United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed

United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed **Chrome yellow (Lead chromate pigment)**

Zinc stearate

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical: Not listed

- Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)** : Listed
- Clean Air Act Section 602 Class I Substances** : Not listed
- Clean Air Act Section 602 Class II Substances** : Not listed
- DEA List I Chemicals (Precursor** : Not listed

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 16 of 19
 Print Date 09/08/2023

Chemicals)

DEA List II Chemicals (Essential Chemicals) : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : EYE IRRITATION - Category 2B
 CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 10 - <= 25	EYE IRRITATION - Category 2B
C.I. Pigment Yellow 34	>= 10 - <= 25	CARCINOGENICITY - Category 1B
Titanium oxide (TiO2)	>= 5 - <= 10	CARCINOGENICITY - Category 2
Quartz (SiO2)	> 0 - <= 0.3	CARCINOGENICITY - inhalation - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
Chrome yellow (Lead chromate pigment)	1344-37-2	>= 10 - < 30

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:
 Calcium carbonate
 Titanium dioxide

New York : None of the components are listed.

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023


Page 17 of 19
 Print Date 09/08/2023

- New Jersey** : The following components are listed:
 Calcium carbonate
 Ethene, chloro-, homopolymer
 Chrome yellow (Lead chromate pigment)
 Titanium dioxide
 Quartz
- Pennsylvania** : The following components are listed:
 Calcium carbonate

 Chrome yellow (Lead chromate pigment)

 Titanium dioxide

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Chrome yellow (Lead chromate pigment), which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Yes.	-
Chrome yellow (Lead chromate pigment)	Yes.	Yes.
Titanium dioxide	-	-
Quartz	-	-

- United States inventory (TSCA 8b)** : All components are active or exempted.
- Canada inventory** : At least one component is not listed in DSL but all such components are listed in NDSL.

International regulations

Inventory list

- Australia** : All components are listed or exempted.
- Canada** : At least one component is not listed in DSL but all such components are listed in NDSL.
- China** : All components are listed or exempted.
- Eurasian Economic Union** : **Russian Federation inventory:** Not determined.
- Japan** : **Japan inventory (CSCL):** Not determined.
Japan inventory (ISHL): Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.

SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
 Revision Date 09/07/2023

Page 18 of 19
 Print Date 09/08/2023

- Taiwan** : All components are listed or exempted. All components are listed or exempted.
- Thailand** : All components are listed or exempted.
- Turkey** : All components are listed or exempted.
- United States** : All components are active or exempted.
- Viet Nam** : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	1
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

- Date of printing** : 09/08/2023
- Date of issue/Date of revision** : 09/07/2023
- Date of previous issue** : 07/25/2023
- Version** : 1.15

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- : BCF = Bioconcentration Factor
- : GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- : IATA = International Air Transport Association
- : IBC = Intermediate Bulk Container
- : IMDG = International Maritime Dangerous Goods
- : LogPow = logarithm of the octanol/water partition coefficient
- : MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- : UN = United Nations

- References** : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the



SAFETY DATA SHEET

030YE11 MUNSELL YELLOW PVC CC

Version Number 1.15
Revision Date 09/07/2023

Page 19 of 19
Print Date 09/08/2023

sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.