

MATERIAL SAFETY DATA SHEET

BLUE 179 MPL 7226

Version Number 1.2 Revision Date 12/19/2003

Page 1 of 6 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BLUE 179 MPL 7226
Product code	:	CC10004124
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	57583-35-4	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET **BLUE 179 MPL 7226**

Version Number 1.2 Revision Date 12/19/2003 Page 2 of 6 Print Date 11/13/2011

Medical Conditions	: None known.	
Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.	at
Skin	: Wash off with soap and plenty of water. If skin irritation persists se medical attention.	el
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fir conditions. 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods.	



MATERIAL SAFETY DATA SHEET **BLUE 179 MPL 7226**

Version Number 1.2 Revision Date 12/19/2003 Page 3 of 6 Print Date 11/13/2011

	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge Hea only in areas with appropriate exhaust ventilation.	t
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	n
8. EXI	OSURE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	: No personal respiratory protective equipment normally required.	
Eye/Face Protection	: Safety glasses with side-shields.	
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved clothing.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety pract Wash hands before breaks and at the end of workday.	ice
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid

Evaporation rate

: Not applicable

POLYONE CORPORATION MATERIAL SAFETY DATA SHEET BLUE 179 MPL 7226 Version Number 1.2 Page 4 of 6 Revision Date 12/19/2003 Print Date 11/13/2011 Appearance : Pellets Specific Gravity: : Not determined Color : BLUE Bulk density Not established Vapor pressure Odor : Very faint : Not applicable Melting point/range : Not determined Vapour density : Not applicable Boiling Point: : Not applicable pН : Not applicable Water solubility : Insoluble **10. STABILITY AND REACTIVITY** Stability : Stable. Hazardous Polymerization Will not occur. Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Avoid contact with strong oxidizers. Also, avoid contact with acetal or Incompatible Materials : acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks. Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : (NOx), hydrogen chloride (HCl), other hazardous materials, and products smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride. **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat	Irritant	Eyes, Skin.
	etradecanoic acid,		
	10-ethyl-4,4-dimethyl-7-o		
	xo-, 2-ethylhexyl ester		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.



MATERIAL SAFETY DATA SHEET **BLUE 179 MPL 7226**

Version Number 1.2 Revision Date 12/19/2003 Page 5 of 6 Print Date 11/13/2011

Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
INIO / INIDO (Inaritine)	
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.



MATERIAL SAFETY DATA SHEET **BLUE 179 MPL 7226**

Version Number 1.2 Revision Date 12/19/2003

Page 6 of 6 Print Date 11/13/2011

SARA Title III Section 302 Extremely Hazardous Substance				
Not applicable				
SARA Title III Section 313 To:	xic (Chemicals:		
Not applicable Canadian Regulations:				
National Pollutant Relea	se Iı	nventory (NPRI)		
Not applicable				
WHMIS Classification	:	D2B		
WHMIS Ingredient Disc	losu	ure List		
CAS-No. 57583-35-4 7631-86-9				
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Listed		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Listed		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.