

## INTENSE ORANGE ES-363

Version Number 1.0  
Revision Date 09/20/2002

Page 1 of 8  
Print Date 11/6/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

**POLYONE CORPORATION**  
33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE : Product Stewardship (770) 271-5902  
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : INTENSE ORANGE ES-363  
Product code : CC10023070  
Chemical Name : Mixture  
CAS-No. : Mixture  
Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components           | CAS-No.    | Weight % |
|----------------------|------------|----------|
| Barium sulfate       | 7727-43-7  | 1 - 5    |
| Selenium             | 7782-49-2  | 1 - 5    |
| C.I. Pigment Red 108 | 58339-34-7 | 10 - 30  |
| Cadmium              | 7440-43-9  | 10 - 30  |

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

#### Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.  
Ingestion : May be harmful if swallowed.  
Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.  
Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

## MATERIAL SAFETY DATA SHEET

**INTENSE ORANGE ES-363**

Version Number 1.0

Page 2 of 8

Revision Date 09/20/2002

Print Date 11/6/2011

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

**4. FIRST AID MEASURES**

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.

**Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

**Flash point** : Not applicable

**Flammable Limits**

- Upper explosion limit : Not applicable
- Lower explosion limit : Not applicable

**Autoignition temperature** : Not relevant

**Suitable extinguishing media** : Carbon dioxide blanket, Water spray, dry powder, foam.

**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : None

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

**Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

**Handling** : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

**INTENSE ORANGE ES-363**

Version Number 1.0

Revision Date 09/20/2002

Page 3 of 8

Print Date 11/6/2011

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective Measures : Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

## MATERIAL SAFETY DATA SHEET

**INTENSE ORANGE ES-363**

Version Number 1.0

Page 4 of 8

Revision Date 09/20/2002

Print Date 11/6/2011

| Components           | Value                    | Exposure time                | Exposure type              | List:   |
|----------------------|--------------------------|------------------------------|----------------------------|---------|
| Barium sulfate       | 10 mg/m <sup>3</sup>     | Time Weighted Average (TWA): | Total dust.                | ACGIH   |
| Barium sulfate       | 5 mg/m <sup>3</sup>      | PEL:                         | Respirable fraction.       | OSHA Z1 |
|                      | 15 mg/m <sup>3</sup>     | PEL:                         | Total dust.                | OSHA Z1 |
| C.I. Pigment Red 108 | 0.005 mg/m <sup>3</sup>  | Time Weighted Average (TWA): | as Cd                      | OSHA    |
|                      | 0.0025 mg/m <sup>3</sup> | OSHA Action level:           | as Cd                      | OSHA    |
|                      | 0.2 mg/m <sup>3</sup>    | PEL:                         | as Se                      | OSHA Z1 |
| C.I. Pigment Red 108 | 0.2 mg/m <sup>3</sup>    | Time Weighted Average (TWA): | as Se                      | MX OEL  |
|                      | 0.01 mg/m <sup>3</sup>   | Time Weighted Average (TWA): |                            | ACGIH   |
| C.I. Pigment Red 108 | 0.2 mg/m <sup>3</sup>    | Time Weighted Average (TWA): |                            | ACGIH   |
| Cadmium              | 0.01 mg/m <sup>3</sup>   | Time Weighted Average (TWA): | Inhalable fraction. as Cd  | ACGIH   |
|                      | 0.002 mg/m <sup>3</sup>  | Time Weighted Average (TWA): | Respirable fraction. as Cd | ACGIH   |
| Cadmium              | 0.005 mg/m <sup>3</sup>  | Time Weighted Average (TWA): | Total as Cd                | OSHA    |
| Selenium             | 0.2 mg/m <sup>3</sup>    | Time Weighted Average (TWA): |                            | ACGIH   |
| Selenium             | 0.2 mg/m <sup>3</sup>    | PEL:                         | as Se                      | OSHA Z1 |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                     |                  |                  |                   |
|---------------------|------------------|------------------|-------------------|
| Form                | : Solid          | Evaporation rate | : Not applicable. |
| Appearance          | : Pellets        | Specific Gravity | : Not determined  |
| Color               | : ORANGE         | Bulk density     | : Not established |
| Odor                | : Very faint     | Vapor pressure   | : Not applicable  |
| Melting point/range | : Not determined | Vapor density    | : Not applicable  |
| Boiling Point:      | : Not applicable | pH               | : Not applicable  |
| Water solubility    | : Insoluble      |                  |                   |

**10. STABILITY AND REACTIVITY**

|                                  |  |
|----------------------------------|--|
| Stability                        | : Stable.  |
| Hazardous Polymerization         | : Will not occur.  |
| Conditions to avoid              | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.   |
| Incompatible Materials           | : Incompatible with strong acids and oxidizing agents.   |
| Hazardous decomposition products | : Carbon dioxide (CO <sub>2</sub> ), carbon monoxide (CO), oxides of nitrogen (NO <sub>x</sub> ), other hazardous materials, and smoke are all possible. |

## MATERIAL SAFETY DATA SHEET

**INTENSE ORANGE ES-363**

Version Number 1.0

Page 5 of 8

Revision Date 09/20/2002

Print Date 11/6/2011

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No.    | Chemical Name        | Effect           | Target Organ   |
|------------|----------------------|------------------|--|
| 7727-43-7  | Barium sulfate       | Irritant         | Respiratory system.  |
|            |                      | Systemic effects | Eyes, Respiratory system.  |
| 7782-49-2  | Selenium             | Systemic effects | Liver, central nervous system, digestive system.   |
| 58339-34-7 | C.I. Pigment Red 108 | Irritant         | Eyes, Skin.  |
| 7440-43-9  | Cadmium              | Systemic effects | Respiratory system, blood and blood forming system, Kidney, urinary system, reproductive system. |
|            |                      | Highly Toxic     | Refer to LC50 / LD50 Data on MSDS..  |

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No.   | Chemical Name | Route     | Value                | Species |
|-----------|---------------|-----------|----------------------|---------|
| 7782-49-2 | Selenium      | Oral LD50 | 6,700 mg/kg          | rat     |
| 7440-43-9 | Cadmium       | LC50      | 25 mg/m <sup>3</sup> | rat     |
|           |               | Oral LD50 | 2,330 mg/kg          | rat     |

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

| CAS-No.    | Chemical Name        | OSHA | IARC | NTP |
|------------|----------------------|------|------|-----|
| 58339-34-7 | C.I. Pigment Red 108 | yes  | 1    | 1   |
| 7440-43-9  | Cadmium              | yes  | 1    | 1   |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

**C.I. Pigment Red 108 58339-34-7 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.**

## INTENSE ORANGE ES-363

Version Number 1.0

Revision Date 09/20/2002

Page 6 of 8

Print Date 11/6/2011

### Additional Health Hazard Information:

**Cadmium 7440-43-9** Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.

### 12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix of the polymer.
- Bioaccumulation Potential : Chemicals are not readily available as they are bound within the matrix of the polymer.
- Additional advice : No data available.

### 13. DISPOSAL CONSIDERATIONS

- Product : Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

### 14. TRANSPORT INFORMATION

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA : Refer to specific regulation.
- IMO / IMDG : Refer to specific regulation.

### 15. REGULATORY INFORMATION

#### US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

## MATERIAL SAFETY DATA SHEET

**INTENSE ORANGE ES-363**

Version Number 1.0

Page 7 of 8

Revision Date 09/20/2002

Print Date 11/6/2011

| Chemical Name | CAS-No.   | % in Product | RQ for component | RQ for Mixture/Product |
|---------------|-----------|--------------|------------------|------------------------|
| Cadmium       | 7440-43-9 | 17.6367      | 010 lbs          | 57 LB                  |

California Proposition 65 : WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

## SARA Title III Section 313 Toxic Chemicals:

| Chemical Name                           | CAS-No.    | Weight % |
|---|------------|----------|
| CADMIUM COMPOUNDS<br>SELENIUM COMPOUNDS | 58339-34-7 | 11.75    |
| CADMIUM                                 | 7440-43-9  | 17.63    |
| ZINC COMPOUNDS                          | 1314-98-3  | 01.17    |
| SELENIUM                                | 7782-49-2  | 03.52    |

## Canadian Regulations:

WHMIS Classification : D1A

## WHMIS Ingredient Disclosure List

| CAS-No.    |
|------------|
| 58339-34-7 |
| 7440-43-9  |
| 7782-49-2  |

DSL : Listed.

## National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Listed.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET

**INTENSE ORANGE ES-363**

Version Number 1.0

Revision Date 09/20/2002

Page 8 of 8

Print Date 11/6/2011

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.