



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CLAY 38/EL

Version Number 1.0
Revision Date 09/11/2003

Page 1 of 7
Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE : Product Stewardship (770) 271-5902
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : CLAY 38/EL
Product code : CC10041716
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Spinels, chromium (III) copper black	68186-91-4	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****CLAY 38/EL**Version Number 1.0
Revision Date 09/11/2003Page 2 of 7
Print Date 11/12/2011**Chronic exposure** : Refer to Section 11 for Toxicological Information.**Medical Conditions
Aggravated by Exposure:** : None known.**4. FIRST AID MEASURES**

- Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point** : Not applicable
- Flammable Limits**
- Upper explosion limit : Not applicable
 - Lower explosion limit : Not applicable
- Autoignition temperature** : Not relevant
- Suitable extinguishing media** : Carbon dioxide blanket, water spray, dry powder, foam.
- Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards** : None

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
- Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CLAY 38/EL

Version Number 1.0
Revision Date 09/11/2003

Page 4 of 7
Print Date 11/12/2011

Appearance	: Pellets	Specific Gravity	: Not determined
Color	: BROWN	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapor density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO ₂), carbon monoxide (CO), oxides of nitrogen (NO _x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
68186-91-4	Spinels, chromium (III) copper black	Irritant	Eyes, Skin, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Additional Health Hazard Information:

Spinels, chromium (III) copper black 68186-91-4 The bi and trivalent forms of chrome have a low order of acute toxicity but may cause dermatitis, pulmonary sensitization and corrosive effect on eyes.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
-------------------------------	------------------------------

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****CLAY 38/EL**Version Number 1.0
Revision Date 09/11/2003Page 5 of 7
Print Date 11/12/2011

Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix of the polymer.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the matrix of the polymer.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO / IMDG : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : This product does not contain a substance listed by California Prop 65.

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****CLAY 38/EL**Version Number 1.0
Revision Date 09/11/2003Page 6 of 7
Print Date 11/12/2011

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
NICKEL COMPOUNDSANTIMONY COMPOUNDS	8007-18-9	0.06
CHROMIUM III COMPOUNDSANTIMONY COMPOUNDS	68186-90-3	1.98
CHROMIUM III COMPOUNDS COPPER COMPOUNDS	68186-91-4	1.71

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Rutile, antimony chromium buff	68186-90-3	1.98	68
Rutile, antimony chromium buff	68186-90-3	1.98	17
Spinel, chromium (III) copper black	68186-91-4	1.71	68
Spinel, chromium (III) copper black	68186-91-4	1.71	70

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
68186-90-3
68186-91-4

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

CLAY 38/EL

Version Number 1.0
Revision Date 09/11/2003

Page 7 of 7
Print Date 11/12/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.