MATERIAL SAFETY DATA SHEET COLOR RICHE CHAMPAGNE

Version Number 1.0 Revision Date 05/13/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	COLOR RICHE CHAMPAGNE
Product code	:	CC10054059
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to 		
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET COLOR RICHE CHAMPAGNE

Version Number 1.0 Revision Date 05/13/2004 Page 2 of 6 Print Date 11/14/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	•	Not applicable
sower explosion limit	•	Not applicable
Autoignition temperature	÷	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

MATERIAL SAFETY DATA SHEET COLOR RICHE CHAMPAGNE

Version Number 1.0 Revision Date 05/13/2004 Page 3 of 6 Print Date 11/14/2011

	ar	nd contamination. Keep in a d	lry, cool place.	
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally	required.
Eye/Face Protection	: Sa	afety glasses with side-shields		
Hand protection	: P1	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		afety practice.
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Mica	20 mppcf	PEL:	Total dust.	
				USHA
	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA ACGIH
Titanium dioxide		Time Weighted Average		
Titanium dioxide	3 mg/m3	Time Weighted Average (TWA): Time Weighted Average		ACGIH
Titanium dioxide	3 mg/m3 10 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA):	Respirable fraction.	ACGIH ACGIH
Titanium dioxide	3 mg/m3 10 mg/m3 15 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA):	Respirable fraction. Total dust.	ACGIH ACGIH
	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Respirable fraction. Total dust.	ACGIH ACGIH OSHA Z1
Form	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(Respirable fraction. Total dust. DPERTIES ration rate : Not	ACGIH ACGIH OSHA Z1
Form Appearance	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not	ACGIH ACGIH OSHA Z1
Form Appearance Color	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YEL	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specif LOW Bulk d	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not	ACGIH ACGIH OSHA Z1
Form Appearance Color Odor	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YELL : Very	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specific LOW Bulk of faint Vapor	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not pressure : Not	ACGIH ACGIH OSHA Z1 applicable determined established applicable
Form Appearance Color Odor Melting point/range	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YELJ : Very : Not c	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Exapo ts Specif LOW Bulk d faint Vapor letermined Vapou	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not pressure : Not r density : Not	ACGIH ACGIH OSHA Z1 applicable determined established applicable applicable
Form Appearance Color Odor	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YELJ : Very : Not c	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specification Specification LOW Bulk do faint Vapor letermined Vapou applicable pH	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not pressure : Not r density : Not	ACGIH ACGIH OSHA Z1 applicable determined established applicable
Form Appearance Color Odor Melting point/range Boiling Point:	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YELL : Very : Not c : Not a : Insol	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specification Specification LOW Bulk do faint Vapor letermined Vapou applicable pH	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not yressure : Not ir density : Not	ACGIH ACGIH OSHA Z1 applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YELI : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Exapo ts Specif LOW Bulk d faint Vapor letermined Vapou upplicable pH uble	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not yressure : Not ir density : Not	ACGIH ACGIH OSHA Z1 applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	3 mg/m3 10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : YELJ : Very : Not c : Not a : Insol 10. S	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO ts Specif LOW Bulk d faint Vapor determined Vapou applicable pH uble	Respirable fraction. Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not yressure : Not ir density : Not	ACGIH ACGIH OSHA Z1 applicable determined established applicable applicable

PolyOne

MATERIAL SAFETY DATA SHEET COLOR RICHE CHAMPAGNE

Version Number 1.0 Revision Date 05/13/2004 Page 4 of 6 Print Date 11/14/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.



MATERIAL SAFETY DATA SHEET COLOR RICHE CHAMPAGNE

Version Number 1.0 Revision Date 05/13/2004 Page 5 of 6 Print Date 11/14/2011

IMO / IMDG (maritime)	:	Refer to specific regulation.		
15. REGULATORY INFORMATION				
US Regulations:				
OSHA Status	:	Classified as hazardous based on components.		
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardous S	Sub	stances (40 CFR 302)		
Not applicable				
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.		
SARA Title III Section 302 Extr	rem	ely Hazardous Substance		
Not applicable				
SARA Title III Section 313 Tox	ic C	Themicals:		
Not applicable Canadian Regulations:				
National Pollutant Release	se Ir	iventory (NPRI)		
Not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Listed		
China IECS	:	Listed		
Europe EINECS	:	Listed		
Japan ENCS	:	Not determined		
Korea KECI	:	Listed		



MATERIAL SAFETY DATA SHEET COLOR RICHE CHAMPAGNE

Version Number 1.0 Revision Date 05/13/2004 Page 6 of 6 Print Date 11/14/2011

Philippines PICCS

: Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.