

## MATERIAL SAFETY DATA SHEET

**604 RED 107**Version Number 1.0  
Revision Date 12/22/2001Page 1 of 8  
Print Date 11/2/2011**1. PRODUCT AND COMPANY IDENTIFICATION**

**POLYONE CORPORATION**  
33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE : Product Stewardship (440)-930-1395  
**Emergency telephone number** : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : 604 RED 107  
 Product code : EM0C904075  
 Chemical Name : Mixture  
 CAS-No. : Mixture  
 Product Use : Industrial Applications

**2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS**

Components	CAS-No.	Weight %
Cadmium selenide (CdSe)	1306-24-7	0.1 - 1
Cadmium sulfide	1306-23-6	0.1 - 1
Caprolactam	105-60-2	1 - 5

**3. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

**POTENTIAL HEALTH EFFECTS**

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

**Acute exposure**

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.  
 Ingestion : May be harmful if swallowed.  
 Eyes : Resin particles, like other inert materials, are mechanically irritating to eyes.  
 Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

## MATERIAL SAFETY DATA SHEET

**604 RED 107**

Version Number 1.0  
Revision Date 12/22/2001

Page 2 of 8  
Print Date 11/2/2011

**Medical Conditions** : None known.  
**Aggravated by Exposure:**

**4. FIRST AID MEASURES**

**Inhalation** : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

**Ingestion** : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

**Eyes** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

**Skin** : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

**5. FIRE-FIGHTING MEASURES**

**Flash point** : Not applicable

**Flammable Limits**

- Upper explosion limit : Not applicable
- Lower explosion limit : Not applicable

**Autoignition temperature** : Not relevant

**Suitable extinguishing media** : Carbon dioxide blanket, Water spray, dry powder, foam.

**Special Fire Fighting Procedures** : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

**Unusual Fire/Explosion Hazards** : None

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

**Environmental precautions** : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

**Methods for cleaning up** : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

**7. HANDLING AND STORAGE**

**Handling** : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

## MATERIAL SAFETY DATA SHEET

**604 RED 107**Version Number 1.0  
Revision Date 12/22/2001Page 3 of 8  
Print Date 11/2/2011

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective Measures : Safety shoes.

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

## MATERIAL SAFETY DATA SHEET

**604 RED 107**Version Number 1.0  
Revision Date 12/22/2001Page 4 of 8  
Print Date 11/2/2011

Components	Value	Exposure time	Exposure type	List:
Cadmium selenide (CdSe)	0.01 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Inhalable fraction. as Cd	ACGIH
	0.002 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Respirable fraction. as Cd	ACGIH
	0.005 mg/m <sup>3</sup>	Time Weighted Average (TWA):		OSHA
	0.0025 mg/m <sup>3</sup>	OSHA Action level:		OSHA
	0.2 mg/m <sup>3</sup>	Time Weighted Average (TWA):		ACGIH
	0.2 mg/m <sup>3</sup>	PEL:	as Se	OSHA Z1
Cadmium sulfide	0.01 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Inhalable fraction. as Cd	ACGIH
	0.002 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Respirable fraction. as Cd	ACGIH
	0.005 mg/m <sup>3</sup>	Time Weighted Average (TWA):		OSHA
Caprolactam	1 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Dust.	ACGIH
	5 ppm 23 mg/m <sup>3</sup>	Time Weighted Average (TWA):	Vapor.	ACGIH
	3 mg/m <sup>3</sup>	Short Term Exposure Limit (STEL):	Dust.	ACGIH
	10 ppm 46 mg/m <sup>3</sup>	Short Term Exposure Limit (STEL):	Vapor.	ACGIH

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Solid	Evaporation rate	: Not applicable.
Appearance	: Pellets, slabs	Specific Gravity	: Not determined
Color	: RED	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapor density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		

**10. STABILITY AND REACTIVITY**

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.

## MATERIAL SAFETY DATA SHEET

**604 RED 107**Version Number 1.0  
Revision Date 12/22/2001Page 5 of 8  
Print Date 11/2/2011

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), other hazardous materials, and smoke are all possible.

**11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1306-24-7	Cadmium selenide (CdSe)	Highly Toxic	Refer to MSDS for Toxicity Data..
1306-23-6	Cadmium sulfide	Highly Toxic	Refer to MSDS for Toxicity Data..
105-60-2	Caprolactam	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, Liver, Kidney, central nervous system, heart or circulatory system.

## LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1306-23-6	Cadmium sulfide	Oral LD50	7,080 mg/kg	rat
105-60-2	Caprolactam	LC50	300 mg/m <sup>3</sup>	rat
		Oral LD50	1,210 mg/kg	rat
		Dermal LD50	1410 ul/kg	rabbit

## Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1306-24-7	Cadmium selenide (CdSe)	yes	1	1
1306-23-6	Cadmium sulfide	yes	1	1

## IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

## NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

**Additional Health Hazard Information:**

## MATERIAL SAFETY DATA SHEET

**604 RED 107**

Version Number 1.0  
Revision Date 12/22/2001

Page 6 of 8  
Print Date 11/2/2011

**Cadmium selenide (CdSe) 1306-24-7 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.**

**Additional Health Hazard Information:**

**Cadmium sulfide 1306-23-6 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.**

**12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: Not applicable

**13. DISPOSAL CONSIDERATIONS**

Product	: Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

**14. TRANSPORT INFORMATION**

U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.

**15. REGULATORY INFORMATION**

## US Regulations:

OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.

## MATERIAL SAFETY DATA SHEET

**604 RED 107**

Version Number 1.0  
Revision Date 12/22/2001

Page 7 of 8  
Print Date 11/2/2011

## US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for Mixture/Product
Cadmium selenide (CdSe)	1306-24-7	3,013 LB

California Proposition 65 : WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

## SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CADMIUM COMPOUNDS SELENIUM COMPOUNDS	1306-24-7	0.33
CADMIUM COMPOUNDS	1306-23-6	0.41

## Canadian Regulations:

WHMIS Classification : D1A

## WHMIS Ingredient Disclosure List

CAS-No.
15782-06-6
1306-24-7
1306-23-6
105-60-2
14808-60-7
57-11-4
14807-96-6

DSL : Listed.

## National Inventories:

Australia AICS : Not determined.  
China IECS : Not determined.  
Europe EINECS : Not determined.  
Japan ENCS : Not determined.  
Korea KECI : Not determined.  
Philippines PICCS : Not determined.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET

**604 RED 107**

Version Number 1.0  
Revision Date 12/22/2001

Page 8 of 8  
Print Date 11/2/2011

**16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.