

SAFETY DATA SHEET**UGLZ6001 UNIGLAZE TAHITI GREEN**

Version Number 1.9
Revision Date 11/10/2022

Page 1 of 20
Print Date 11/11/2022

SAFETY DATA SHEET**UGLZ6001 UNIGLAZE TAHITI GREEN****Section 1. Identification**

GHS product identifier : UGLZ6001 UNIGLAZE TAHITI GREEN
Chemical name : Mixture
CAS number : Mixture
Other means of identification : FO00016735
Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **AVIENT CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012
 1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
 ACUTE TOXICITY (inhalation) - Category 4
 EYE IRRITATION - Category 2A
 CARCINOGENICITY - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 67.4 %

Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 65 %

Percentage of the mixture consisting of ingredient(s) of unknown

SAFETY DATA SHEET**UGLZ6001 UNIGLAZE TAHITI GREEN**

Version Number 1.9
Revision Date 11/10/2022

Page 2 of 20
Print Date 11/11/2022

acute inhalation toxicity: 68.8 %

GHS label elements**Hazard pictograms****Signal word****Hazard statements**

- : Warning
- : Flammable liquid and vapor.
- : Causes serious eye irritation.
- : Harmful if inhaled.
- : Suspected of causing cancer.

Precautionary statements**Prevention****Response****Storage****Disposal****Supplemental label elements****Hazards not otherwise classified**

- : Not applicable.
- : Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapor.
- : IF exposed or concerned: Get medical advice or attention. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- : Store in a well-ventilated place. Keep cool.
- : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- : None known.
- : None known.
- : Not available.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Chemical name** : Mixture
- Other means of identification** : FO00016735

CAS number/other identifiers

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 3 of 20
Print Date 11/11/2022

| Ingredient name | % | CAS number |
|---|---------------|------------|
| Titanium dioxide | >= 10 - <= 25 | 13463-67-7 |
| Solvent naphtha, petroleum, light arom. | >= 5 - <= 10 | 64742-95-6 |
| 2-Butoxy ethanol | >= 5 - <= 10 | 111-76-2 |
| Benzene, 1,2,4-trimethyl- | >= 1 - <= 3 | 95-63-6 |
| Cumene | > 0 - <= 0.3 | 98-82-8 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 4 of 20
 Print Date 11/11/2022

material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 5 of 20
Print Date 11/11/2022

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

Specific hazards arising from the chemical : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

SAFETY DATA SHEET**UGLZ6001 UNIGLAZE TAHITI GREEN**

Version Number 1.9
Revision Date 11/10/2022

Page 6 of 20
Print Date 11/11/2022

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 7 of 20
 Print Date 11/11/2022

oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|---|--|
| Titanium dioxide | OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3 |
| Solvent naphtha, petroleum, light arom. | None. |
| 2-Butoxy ethanol | OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 120 mg/m3 25 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 240 mg/m3 50 ppm |
| Benzene, 1,2,4-trimethyl- | NIOSH REL (1994-06-01) TWA 125 mg/m3 25 ppm OSHA PEL 1989 (1989-03-01) TWA 125 mg/m3 25 ppm ACGIH TLV (1994-09-01) TWA 123 mg/m3 25 ppm |
| Cumene | OSHA PEL 1989 (1989-03-01) Absorbed through skin. TWA 245 mg/m3 50 ppm OSHA PEL (1993-06-30) Absorbed through skin. TWA 245 mg/m3 50 ppm |

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 8 of 20
Print Date 11/11/2022

statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 9 of 20
Print Date 11/11/2022

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

| | | |
|--|---|--|
| Physical state | : | liquid [liquid] |
| Color | : | NOT APPLICABLE |
| Odor | : | Not available. |
| Odor threshold | : | Not available. |
| pH | : | Not available. |
| Melting point | : | Not available. |
| Boiling point | : | Not available. |
| Flash point | : | 123 °F (51 °C) |
| | | |
| Burning time | : | Not available. |
| Burning rate | : | Not available. |
| Evaporation rate | : | Not available. |
| Flammability (solid, gas) | : | Not available. |
| Lower and upper explosive (flammable) limits | : | Lower: Not available. Upper: Not available. |
| Vapor pressure | : | Not available. |
| Vapor density | : | Not available. |
| Relative density | : | Not available. |
| Solubility | : | Not available. |
| Solubility in water | : | Not available. |
| Partition coefficient: n-octanol/water | : | Not available. |
| Auto-ignition temperature | : | Not available. |
| Decomposition temperature | : | Not available. |
| SADT | : | Not available. |
| Viscosity | : | Dynamic: Not available. Kinematic: Not available. |

Aerosol product

| | | |
|--|---|----------------|
| Heat of combustion | : | Not available. |
| | | |
| Ignition distance | : | Not available. |
| Enclosed space ignition - Time equivalent | : | Not available. |
| Enclosed space ignition - Deflagration density | : | Not available. |
| Flame height | : | Not available. |
| Flame duration | : | Not available. |

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 10 of 20
Print Date 11/11/2022

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials** : Reactive or incompatible with the following materials:
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information**Information on toxicological effects****Acute toxicity**

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|------------------------------------|------------|---------------|----------|
| Titanium oxide (TiO ₂) | | | | |
| | LC50 Inhalation Dusts and mists | Rat - Male | 6.82 Mg/l | 4 h |
| | LD50 Dermal | Rabbit | > 5,000 mg/kg | - |
| Solvent naphtha (petroleum), light arom. | | | | |
| | LD50 Oral | Rat | 8,400 mg/kg | - |
| Ethanol, 2-butoxy- | | | | |
| | LD50 Oral | Rat | 250 mg/kg | - |
| | LC50 Inhalation Gas. | Rat | 450 ppm | 4 h |
| | LD50 Dermal | Rabbit | 220 mg/kg | - |
| Benzene, 1,2,4-trimethyl- | | | | |
| | LD50 Oral | Rat | 5,000 mg/kg | - |
| | LC50 Inhalation Vapor | Rat | 18 Mg/l | 4 h |
| Benzene, (1-methylethyl)- | | | | |
| | LD50 Oral | Rat | 1,400 mg/kg | - |
| | LC50 Inhalation Vapor | Rat | 39 Mg/l | 4 h |

Conclusion/Summary : Mixture. Not fully tested.

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 11 of 20
 Print Date 11/11/2022

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|----------|-------------|
| Solvent naphtha (petroleum), light arom. | Eyes - Mild irritant | Rabbit | - | 24 hrs | - |
| Ethanol, 2-butoxy- | Eyes - Moderate irritant | Rabbit | - | 24 hrs | - |
| | Eyes - Severe irritant | Rabbit | - | | - |
| | Skin - Mild irritant | Rabbit | - | | - |
| Benzene, (1-methylethyl)- | Eyes - Mild irritant | Rabbit | - | 24 hrs | - |
| | Skin - Mild irritant | Rabbit | - | 24 hrs | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hrs | - |
| | Eyes - Mild irritant | Rabbit | - | | - |

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|---------------------------|------|------|--|
| Titanium oxide (TiO2) | - | 2B | - |
| Ethanol, 2-butoxy- | - | 3 | - |
| Benzene, (1-methylethyl)- | - | 2B | Reasonably anticipated to be a human carcinogen. |

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 12 of 20
 Print Date 11/11/2022

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Name | Result |
|--|--------------------------------|
| Solvent naphtha (petroleum), light arom. | ASPIRATION HAZARD - Category 1 |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Harmful if inhaled.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following: pain or irritation, watering, redness
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 13 of 20
 Print Date 11/11/2022

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Product/ingredient name | Oral | Dermal | Inhalation (gases) | Inhalation (vapors) | Inhalation (dusts and mists) |
|--|-------------|---------------|--------------------|---------------------|------------------------------|
| UGLZ6001 UNIGLAZE TAHITI GREEN | 2,818 mg/kg | 2,480.7 mg/kg | 5,249.2 ppm | 605 Mg/l | N/A |
| Titanium oxide (TiO2) | N/A | N/A | N/A | N/A | 6.82 Mg/l |
| Solvent naphtha (petroleum), light arom. | 8,400 mg/kg | N/A | N/A | N/A | N/A |
| Ethanol, 2-butoxy- | 250 mg/kg | 220 mg/kg | 450 ppm | N/A | N/A |
| Benzene, 1,2,4-trimethyl- | 5,000 mg/kg | N/A | N/A | 18 Mg/l | N/A |
| Benzene, (1-methylethyl)- | 1,400 mg/kg | N/A | N/A | 39 Mg/l | N/A |

- Other information** : This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---|----------------------------------|----------|
| Titanium oxide (TiO2) | Acute LC50 > 1,000 Mg/l Marine water | Fish - Fundulus heteroclitus | 96 h |
| | Acute LC50 3 Mg/l Fresh water | Crustaceans - Ceriodaphnia dubia | 48 h |

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 14 of 20
Print Date 11/11/2022

| | | | |
|---------------------------|-------------------------------------|-------------------------------------|------|
| | Acute LC50 6.5 Mg/l Fresh water | Daphnia - Daphnia pulex | 48 h |
| Ethanol, 2-butoxy- | | | |
| | Acute LC50 1,250 Mg/l Marine water | Fish - Menidia beryllina | 96 h |
| | Acute EC50 > 1,000 Mg/l Fresh water | Daphnia - Daphnia magna | 48 h |
| | Acute LC50 800 Mg/l Marine water | Crustaceans - Crangon crangon | 48 h |
| Benzene, 1,2,4-trimethyl- | | | |
| | Acute LC50 7.72 Mg/l Fresh water | Fish - Pimephales promelas | 96 h |
| | Acute LC50 4.91 Mg/l Marine water | Crustaceans - Elasmopus pecteniscus | 48 h |
| Benzene, (1-methylethyl)- | | | |
| | Acute LC50 0.0027 Mg/l Fresh water | Fish - Oncorhynchus mykiss | 96 h |
| | Acute EC50 7.4 Mg/l Marine water | Crustaceans - Artemia sp. | 48 h |
| | Acute EC50 10.6 Mg/l Fresh water | Daphnia - Daphnia magna | 48 h |

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------|------------------|-----------|
| Solvent naphtha (petroleum), light arom. | - | 10.00 - 2,500.00 | high |
| Ethanol, 2-butoxy- | 0.81 | - | low |
| Benzene, 1,2,4-trimethyl- | 3.63 | 243.00 | low |
| Benzene, (1-methylethyl)- | 3.55 | 35.48 | low |

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 15 of 20
 Print Date 11/11/2022

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : In accordance with 49CFR 173.150(f)(1) and (2), non-bulk quantities of this material may be shipped as non-regulated for USA domestic highway transport only.

International Air ICAO/IATA : UN1866, Resin Solution, 3, PGIII

International Water IMO/IMDG : UN1866, Resin Solution, 3, PGIII

Section 15. Regulatory information

U.S. Federal regulations : **United States - TSCA 12(b) - Chemical export notification:** None of the components are listed.
United States - TSCA 4(a) - Final Test Rules: Not listed

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 16 of 20
 Print Date 11/11/2022

United States - TSCA 4(a) - ITC Priority list: Not listed
 United States - TSCA 4(a) - Proposed test rules: Not listed
 United States - TSCA 4(f) - Priority risk review: Not listed
 United States - TSCA 5(a)2 - Final significant new use rules: Not listed
 United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed
 United States - TSCA 5(e) - Substances consent order: Not listed
 United States - TSCA 6 - Final risk management: Not listed
 United States - TSCA 6 - Proposed risk management: Not listed
 United States - TSCA 8(a) - Chemical risk rules: Not listed
 United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed
 United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
 United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed 2-Propanol, 1-methoxy-, 2-acetate Poly(dimethylsiloxane)

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
 United States - TSCA 8(d) - Health and safety studies: Not listed
 United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Phthalocyanine green Phthalocyanine Blue

United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed
 United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
 United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
 United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Listed
 Clean Air Act Section 602 Class I Substances : Not listed
 Clean Air Act Section 602 Class II Substances : Not listed
 DEA List I Chemicals (Precursor Chemicals) : Not listed
 DEA List II Chemicals (Essential Chemicals) : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 17 of 20
 Print Date 11/11/2022

not applicable

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3
 ACUTE TOXICITY - inhalation - Category 4
 EYE IRRITATION - Category 2A
 CARCINOGENICITY - Category 2

Composition/information on ingredients

| Name | % | Classification |
|--|---------------|--|
| Titanium oxide (TiO2) | >= 10 - <= 25 | CARCINOGENICITY - Category 2 |
| Solvent naphtha (petroleum), light arom. | >= 5 - <= 10 | FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2B ASPIRATION HAZARD - Category 1 |
| Ethanol, 2-butoxy- | >= 5 - <= 10 | FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY - oral - Category 3 ACUTE TOXICITY - dermal - Category 3 ACUTE TOXICITY - inhalation - Category 2 EYE IRRITATION - Category 2A |
| 2-Propanol, 1-methoxy-, 2-acetate | >= 5 - <= 8.3 | FLAMMABLE LIQUIDS - Category 3 |
| Benzene, 1,2,4-trimethyl- | >= 1 - <= 3 | FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4 |
| Benzene, (1-methylethyl)- | > 0 - <= 0.3 | FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2B CARCINOGENICITY - Category 2 |

Form R - Reporting requirements

| Product name | CAS number | % |
|---------------------------|------------|--------------|
| 2-Butoxy ethanol | 111-76-2 | >= 5 - <= 10 |
| Benzene, 1,2,4-trimethyl- | 95-63-6 | >= 1 - <= 3 |
| Cumene | 98-82-8 | > 0 - <= 0.3 |

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 18 of 20
Print Date 11/11/2022

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

State regulations

- Massachusetts** : None of the components are listed.
- New York** : The following components are listed:
Cumene
- New Jersey** : The following components are listed:
Titanium dioxide
Solvent naphtha, petroleum, light arom.
2-Butoxy ethanol
Phthalocyanine green
Benzene, 1,2,4-trimethyl-
Phthalocyanine Blue
Cumene
- Pennsylvania** : The following components are listed:
Titanium dioxide

2-Butoxy ethanol


Phthalocyanine green

Benzene, 1,2,4-trimethyl-

Phthalocyanine Blue

Cumene

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

| Ingredient name | No significant risk level | Maximum acceptable dosage level |
|------------------|---------------------------|---------------------------------|
| Titanium dioxide | - | - |
| Cumene | - | - |

United States inventory (TSCA 8b) : All components are active or exempted.

Canada inventory : At least one component is not listed in DSL but all such components are listed in NDSL.

International regulations

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
 Revision Date 11/10/2022

Page 19 of 20
 Print Date 11/11/2022

Inventory list

- Australia** : Not determined.
- Canada** : At least one component is not listed in DSL but all such components are listed in NDSL.
- China** : All components are listed or exempted.
- Europe inventory** : All components are listed or exempted.
- Japan** : Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : Not determined.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Turkey** : Not determined.
- United States** : All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

| | | |
|-------------------------|---|---|
| Health | * | 2 |
| Flammability | | 2 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

- Date of printing** : 11/11/2022
- Date of issue/Date of revision** : 11/10/2022
- Date of previous issue** : 10/27/2022
- Version** : 1.9

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- : BCF = Bioconcentration Factor
- : GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- : IATA = International Air Transport Association
- : IBC = Intermediate Bulk Container
- : IMDG = International Maritime Dangerous Goods
- : LogPow = logarithm of the octanol/water partition coefficient
- : MARPOL = International Convention for the Prevention of Pollution From

SAFETY DATA SHEET

UGLZ6001 UNIGLAZE TAHITI GREEN

Version Number 1.9
Revision Date 11/10/2022

Page 20 of 20
Print Date 11/11/2022

References

: Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations
Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.