MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0 Revision Date 08/06/2003 Page 1 of 8 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

| NON-EMERGENCY TELEPHONE | : | Product Stewardship, (314) 771-1800 |
|-------------------------------|---|------------------------------------------------------------------------------|
| Emergency telephone number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name | : | STAN-TONE VC-29306 TITANIUM |
| Product code | : | FO20005891 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|------------|----------|
| Carbon black | 1333-86-4 | 0.1 - 1 |
| Calcium carbonate | 1317-65-3 | 1 - 5 |
| Mica | 12001-26-2 | 1 - 5 |
| Stoddard solvent | 8052-41-3 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Aluminum | 7429-90-5 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute exposure | |
| Inhalation Ingestion Eyes Skin | Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. |

PolyOne

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0 Revision Date 08/06/2003 Page 2 of 8 Print Date 11/11/2011

| Medical Conditions : None known. Aggravated by Exposure: | | |
|--------------------------------------------------------------------------------------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | 4. FIRST AID MEASURES |
| Inhalation | : | Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : | Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : | Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | | 5. FIRE-FIGHTING MEASURES |
| Flash point | : | Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | : : : | Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. |
| Special Fire Fighting Procedures | : | Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | : | May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. |
| | 6. A | CCIDENTAL RELEASE MEASURES |
| Personal precautions | : | Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : | Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : | Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0 Revision Date 08/06/2003

Page 3 of 8 Print Date 11/11/2011

| | | 7. HANDLING AND STORAGE |
|-----------------------------------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
| 8. EXP | OSU | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection. |
| Eye/Face Protection | : | Safety glasses with side-shields. |
| Hand protection | : | Protective gloves. |
| Skin and body protection | : | Long sleeved clothing. |
| Additional Protective Measures | : | Safety shoes. |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0

Revision Date 08/06/2003

Page 4 of 8 Print Date 11/11/2011

| Components | Value | Exposure time | Exposure type | List: |
|-------------------|---------------------------|------------------------------|--------------------------------|---------|
| Aluminum | 10 mg/m3 | Time Weighted Average (TWA): | Dust. | ACGIH |
| | 5 mg/m3 | Time Weighted Average (TWA): | Welding fume. as Al | ACGIH |
| Aluminum | 15 mg/m3 | PEL: | Total dust. as Al | OSHA Z1 |
| | 5 mg/m3 | PEL: | Respirable dust. as Al | OSHA Z1 |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| Carbon black | 3.5 mg/m3 | Time Weighted Average (TWA): | Total dust. as carbon black | ACGIH |
| Carbon black | 3.5 mg/m3 | PEL: | Total dust. as carbon black | OSHA Z1 |
| Mica | 20 mppcf | PEL: | Total dust. | OSHA |
| | 3 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | ACGIH |
| Stoddard solvent | 100 ppm 525 mg/m3 | Time Weighted Average (TWA): | Vapor and mist. | ACGIH |
| Stoddard solvent | 500 ppm 2,900 mg/m3 | PEL: | Vapor and mist. | OSHA Z1 |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| Titanium dioxide | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

: powder, granular : GREY : Very faint : Not determined Not applicable : Insoluble

: Solid

:

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН

- : Not applicable. : Not determined
- : Not determined
- : Not applicable
- : Not applicable
- Not applicable :

10. STABILITY AND REACTIVITY

| Stability | : | Stable. |
|----------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes |

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0 Revision Date 08/06/2003 Page 5 of 8 Print Date 11/11/2011

or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|-------------------|------------------|---------------------------------|
| 1333-86-4 | Carbon black | Systemic effects | Eyes, Respiratory system. |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |
| 12001-26-2 | Mica | Systemic effects | Respiratory system. |
| 8052-41-3 | Stoddard solvent | Systemic effects | Eyes, Skin, Respiratory system, |
| | | | Kidney, central nervous |
| | | | system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 7429-90-5 | Aluminum | Irritant | Skin, Respiratory system. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|---------------|-------------|----------------|---------|
| 1333-86-4 | Carbon black | Oral LD50 | > 15,400 mg/kg | rat |
| | | Dermal LD50 | > 3 gm/kg | rabbit |

Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|-----------|---------------|------|------|-----|
| 1333-86-4 | Carbon black | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0 Revision Date 08/06/2003 Page 6 of 8 Print Date 11/11/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

| Persistence and degradability | : Not readily biodegradable. |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Toxicity | : Adverse ecological impact is not known or expected under normal use |
| Bioaccumulation Potential | : No data available. |
| Additional advice | : No data available. |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Not regulated for transportation. |
| ICAO/IATA | : Not regulated for transportation. |
| IMO / IMDG | : Not regulated for transportation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29306 TITANIUM

Version Number 1.0 Revision Date 08/06/2003 Page 7 of 8 Print Date 11/11/2011

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name | CAS-No. | Weight % |
|-------------------------|-----------|----------|
| ALUMINUM (FUME OR DUST) | 7429-90-5 | 6.04 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight % | NPRI ID# |
|----------------------------|---------------|----------|----------|
| Aluminum | 7429-90-5 | 6.04 | 12 |
| Misc00005- Misc Zinc Cpd's | Not Available | 0.15 | 241 |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|------------|--|
| 7429-90-5 | |
| 12001-26-2 | |
| 8052-41-3 | |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Not determined. |
|----------------|---|-----------------|
| China IECS | : | Not determined. |
| Europe EINECS | : | Not determined. |
| Japan ENCS | : | Not determined. |

:

| YONE CORPORA | ATION | TOIYONC. |
|------------------------------------------|----------------------------|-------------------------------------------------------|
| RIAL SAFETY DATA SH | | |
| N-TONE VC-2930 | 6 TITANIUM | |
| n Number 1.0 on Date 08/06/2003 | | Page 8 o Print Date 11/11/20 |
| | | |
| Korea KECI | : Not determined. | |
| Philippines PICCS | : Not determined. | |
| | 16. OTHER INF | FORMATION |
| aterial when used in combin nditions. | nation with any other mate | erials and/or in any particular process or processing |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |