

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 1 of 20
Print Date 05/06/2015

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Section 1. Identification

GHS product identifier : STAN-TONE VCP-35249 ORANGE
Chemical name : Mixture
CAS number : Mixture
Other means of identification : FO20034219
Product type : solid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **POLYONE CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012
 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation) : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : COMBUSTIBLE DUSTS
 CARCINOGENICITY - Category 1A

GHS label elements

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 2 of 20
Print Date 05/06/2015

Hazard pictograms

:


Signal word

:

Danger

Hazard statements

:

May form combustible dust concentrations in air.
May cause cancer.

Precautionary statements
General

:

Not applicable.

Prevention

:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response

:

IF exposed or concerned: Get medical attention.

Storage

:

Store in a well-ventilated place.

Disposal

:

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

:

Keep container tightly closed.

Hazards not otherwise classified

:

Fine dust clouds may form explosive mixtures with air. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients
Substance/mixture

:

Mixture

Chemical name

:

Mixture

Other means of identification

:

FO20034219

CAS number/other identifiers

Ingredient name	%	CAS number
Lead chromate	30 - 60	7758-97-6
Molybdate orange (Lead chromate pigment)	10 - 30	12656-85-8
Titanium dioxide	5 - 10	13463-67-7

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 3 of 20
Print Date 05/06/2015

Lead sulfate	1 - 5	7446-14-2
Miscellaneous Cadmium Compounds	0.1 - 1	Not available.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SAFETY DATA SHEET**STAN-TONE VCP-35249 ORANGE**

Version Number 1.1
Revision Date 05/04/2015

Page 4 of 20
Print Date 05/06/2015

Most important symptoms/effects, acute and delayed**Potential acute health effects**

- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures**Extinguishing media**

- Suitable extinguishing media** : Use dry chemical powder.
- Unsuitable extinguishing media** : Do not use water jet.

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 5 of 20
Print Date 05/06/2015

- Specific hazards arising from the chemical** : Fine dust clouds may form explosive mixtures with air.
- Hazardous thermal decomposition products** : May emit Hydrogen Chloride (HCl).
Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
sulfur oxides
halogenated compounds
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed,

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 6 of 20
Print Date 05/06/2015

Large spill

- labeled waste container. Dispose of via a licensed waste disposal contractor.
- : Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 7 of 20
Print Date 05/06/2015

ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Lead chromate	<p>ACGIH TLV (2012-03-05) Calculated as Cr TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.012 mg/m³</p> <p>ACGIH TLV (1994-09-01) Calculated as Pb TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.05 mg/m³</p> <p>OSHA PEL (2006-11-27) Calculated as Cr PEL: Permissible Exposure Level 0.005 mg/m³</p> <p>OSHA PEL Z2 (2006-11-27) Ceiling 0.001 mg/m³</p> <p>NIOSH REL (2010-09-01) Calculated as Cr Time Weighted Average (TWA) 0.0002 mg/m³</p> <p>OSHA PEL 1989 (1989-03-01) Calculated as CrO₃ Ceiling 0.1 mg/m³</p> <p>OSHA PEL 1989 (1989-03-01) Calculated as Pb PEL: Permissible Exposure Level 0.075 mg/m³</p>
Molybdate orange (Lead chromate pigment)	<p>OSHA PEL (1993-06-30) Calculated as Mo PEL: Permissible Exposure Level 15 mg/m³ Form: Total dust</p> <p>OSHA PEL (2006-11-27) Calculated as Cr PEL: Permissible Exposure Level 0.005 mg/m³</p> <p>OSHA PEL Z2 (2006-11-27) Ceiling 0.001 mg/m³</p> <p>NIOSH REL (2010-09-01) Calculated as Cr Time Weighted Average (TWA) 0.0002 mg/m³</p> <p>Time Weighted Average (TWA) 0.5 mg/m³</p> <p>OSHA PEL 1989 (1989-03-01) Calculated as CrO₃ Ceiling 0.1 mg/m³</p> <p>OSHA PEL 1989 (1989-03-01) Calculated as Pb PEL: Permissible Exposure Level 0.075 mg/m³</p> <p>OSHA PEL 1989 (1989-03-01) Calculated as Mo PEL: Permissible Exposure Level 10 mg/m³ Form: Total dust</p>

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 8 of 20
Print Date 05/06/2015

	<p>OSHA PEL 1989 (1989-03-01) Calculated as Cr PEL: Permissible Exposure Level 0.5 mg/m³ ACGIH TLV (1995-05-23) Calculated as Pb TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.05 mg/m³ ACGIH TLV (2001-02-22) Calculated as Mo TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m³ Form: Inhalable fraction TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 3 mg/m³ Form: Respirable fraction</p>
Titanium dioxide	<p>OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m³ Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m³ Form: Total dust ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m³</p>
Lead sulfate	<p>OSHA PEL 1989 (1989-03-01) Calculated as Pb PEL: Permissible Exposure Level 0.075 mg/m³ ACGIH TLV (1995-05-23) Calculated as Pb TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.05 mg/m³</p>
Miscellaneous Cadmium Compounds	<p>NIOSH REL (1994-06-01) Calculated as Cd Form: Fume ACGIH TLV (1994-09-01) Calculated as Cd TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.01 mg/m³ Form: Inhalable fraction TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 0.002 mg/m³ Form: Respirable fraction</p>

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

SAFETY DATA SHEET**STAN-TONE VCP-35249 ORANGE**

Version Number 1.1
Revision Date 05/04/2015

Page 9 of 20
Print Date 05/06/2015

necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties**Appearance**

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 10 of 20
Print Date 05/06/2015

Physical state	: solid [Powder.]
Color	: ORANGE
Odor	: Not available.
Odor threshold	: Not available.
pH	: Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Not available.
Burning time	: Not available.
Burning rate	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: Not available. Upper: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Dynamic: Not available. Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	: Avoid contact with acetal homopolymers and acetyl homopolymers during processing.

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 11 of 20
Print Date 05/06/2015

Hazardous decomposition products : Reactive or incompatible with the following materials:
oxidizing materials
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Lead sulfate				
Miscellaneous Cadmium Compounds				
	LD50 Oral	Rat	72 mg/kg	-

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Conclusion/Summary

Skin : Mixture.Not fully tested.
Eyes : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin : Mixture.Not fully tested.
Respiratory : Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 12 of 20
Print Date 05/06/2015

Product/ingredient name	OSHA	IARC	NTP
Lead chromate	+	1	Known to be a human carcinogen.Reasonably anticipated to be a human carcinogen.
Molybdate orange (Lead chromate pigment)	+	1	
Titanium dioxide		2B	
Lead sulfate		2A	
Miscellaneous Cadmium Compounds	+	1	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
- Inhalation** : Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
irritation
redness

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 13 of 20
Print Date 05/06/2015

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

- Conclusion/Summary** : Mixture. Not fully tested.
- General** : Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide			

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1

Page 14 of 20

Revision Date 05/04/2015

Print Date 05/06/2015

	Acute LC50 > 1,000,000 µg/l Marine water	Fish - Mummichog	96 h
	Acute LC50 > 1,000 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 35.306 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
Lead sulfate			
	Acute LC50 148 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 750 µg/l Marine water	Fish - Red Tongue Sole	96 h
	Acute LC50 60,800 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 6,240 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 148,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 0.392 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute IC50 82 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute IC50 360 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute IC50 400 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 395 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
Miscellaneous Cadmium Compounds			
	Acute LC50 9,350 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 10,470 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 9,920 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 7,029 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 177 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 3,280 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 0.0054 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h

Conclusion/Summary : Not available.

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 15 of 20
Print Date 05/06/2015

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Molybdate orange (Lead chromate pigment)		3,600.00	high
Titanium dioxide		352.00	low
Miscellaneous Cadmium Compounds		1,345.00	high

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.
Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 16 of 20
Print Date 05/06/2015

U.S. DOT Classification : Not regulated for transportation.
ICAO/IATA : Consult mode specific transport rules
IMO/IMDG (maritime) : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations :

- United States - TSCA 12(b) - Chemical export notification:** None of the components are listed.
- United States - TSCA 4(a) - Final Test Rules:** Not listed
- United States - TSCA 4(a) - ITC Priority list:** Not listed
- United States - TSCA 4(a) - Proposed test rules:** Not listed
- United States - TSCA 4(f) - Priority risk review:** Not listed
- United States - TSCA 5(a)2 - Final significant new use rules:** Not listed
- United States - TSCA 5(a)2 - Proposed significant new use rules:** Listed **Lead chromate**
Molybdate orange (Lead chromate pigment)
Lead sulfate
- United States - TSCA 5(e) - Substances consent order:** Not listed
- United States - TSCA 6 - Final risk management:** Listed **Lead chromate**
Molybdate orange (Lead chromate pigment)
- United States - TSCA 6 - Proposed risk management:** Not listed
- United States - TSCA 8(a) - Chemical risk rules:** Not listed
- United States - TSCA 8(a) - Dioxin/Furane precursor:** Not listed
- United States - TSCA 8(a) - Chemical Data Reporting (CDR):** Not determined
- United States - TSCA 8(a) - Preliminary assessment report (PAIR):** Not listed
- United States - TSCA 8(c) - Significant adverse reaction (SAR):** Not listed
- United States - TSCA 8(d) - Health and safety studies:** Not listed
- United States - EPA Clean water act (CWA) section 307 - Priority pollutants:** Listed **Lead chromate**
Molybdate orange (Lead chromate pigment)
Lead sulfate
Miscellaneous Cadmium Compounds
Phenol
Vinyl chloride monomer

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 17 of 20
Print Date 05/06/2015

United States - EPA Clean water act (CWA) section 311 -
Hazardous substances: Listed
United States - EPA Clean air act (CAA) section 112 - Accidental
release prevention - Flammable substances: Not listed
United States - EPA Clean air act (CAA) section 112 - Accidental
release prevention - Toxic substances: Not listed
United States - Department of commerce - Precursor chemical:
Not listed

Clean Air Act Section 112(b) : Listed
Hazardous Air Pollutants (HAPs)
Clean Air Act Section 602 Class I : Not listed
Substances
Clean Air Act Section 602 Class II : Not listed
Substances
DEA List I Chemicals (Precursor : Not listed
Chemicals)
DEA List II Chemicals (Essential : Not listed
Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Lead sulfate	7446-14-2	10 lb(s) 4.54 kg

SARA 311/312

Classification : Fire hazard
Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
Lead chromate	30 - 60	CH
Molybdate orange (Lead chromate pigment)	10 - 30	CH
Titanium dioxide	5 - 10	CH
Lead sulfate	1 - 5	F, CH
Miscellaneous Cadmium	0.1 - 1	AH, CH

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 18 of 20
Print Date 05/06/2015

Compounds		
------------------	--	--

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Lead chromate	7758-97-6	30 - 60
	Molybdate orange (Lead chromate pigment)	12656-85-8	10 - 30
	Lead sulfate	7446-14-2	1 - 5
	Miscellaneous Cadmium Compounds		0.1 - 1
Supplier notification	Lead chromate	7758-97-6	30 - 60
	Molybdate orange (Lead chromate pigment)	12656-85-8	10 - 30
	Lead sulfate	7446-14-2	1 - 5
	Miscellaneous Cadmium Compounds		0.1 - 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations**Massachusetts**

- : The following components are listed:
Lead chromate
Titanium dioxide
Lead sulfate

New York

- : The following components are listed:
Lead sulfate
Miscellaneous Cadmium Compounds

New Jersey

- : The following components are listed:
Lead chromate
Ethene, chloro-, homopolymer
Molybdate orange (Lead chromate pigment)
Titanium dioxide
Lead sulfate
Miscellaneous Cadmium Compounds

Pennsylvania

- : The following components are listed:
Lead chromate

Molybdate orange (Lead chromate pigment)

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 19 of 20
Print Date 05/06/2015

Titanium dioxide

Lead sulfate

Miscellaneous Cadmium Compounds

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations

International lists :

- Australia inventory (AICS):** Not determined.
- Taiwan inventory (CSNN):** Not determined.
- Malaysia Inventory (EHS Register):** Not determined.
- EINECS:** Not determined.
- Japan inventory:** Not determined.
- China inventory (IECSC):** Not determined.
- Korea inventory:** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

Section 16. Other information

History

Date of printing : 05/06/2015
Date of issue/Date of revision : 05/04/2015
Date of previous issue : 12/04/2014
Version : 1.1

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association

SAFETY DATA SHEET

STAN-TONE VCP-35249 ORANGE

Version Number 1.1
Revision Date 05/04/2015

Page 20 of 20
Print Date 05/06/2015

IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations
: Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.