

CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 1 of 18 Print Date 07/18/2023

# SAFETY DATA SHEET

#### CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Section 1. Identification	on	
GHS product identifier	:	CORE™ DB5667 STATIC DISSIPATIV PVCBLK122
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20049142
Product type	:	liquid
Relevant identified uses of the subs	stance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	EYE IRRITATION - Category 2B SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1B

#### **GHS label elements**



## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 2 of 18 Print Date 07/18/2023

Hazard pictograms	:	
Signal word Hazard statements	:	Danger May cause an allergic skin reaction. Causes eye irritation. May cause cancer.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must
Response	:	not be allowed out of the workplace. IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20049142

#### CAS number/other identifiers

Ingredient name	%	CAS number
Diundecyl phthalate	>= 25 - <= 50	3648-20-2
Antimony trioxide	>= 3 - <= 5	1309-64-4



# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 3 of 18 Print Date 07/18/2023

Proprietary Hazardous Compounds	>= 0.3 - < 1	Not available.
Carbon black	> 0 - <= 0.3	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

# **ÀVIENT**

# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 4 of 18 Print Date 07/18/2023

#### Potential acute health effects

Eye contact Inhalation Skin contact	<ul> <li>Causes eye irritation.</li> <li>No known significant effects or critical hazards.</li> <li>May cause an allergic skin reaction.</li> </ul>
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: Adverse symptoms may include the following: irritation watering redness
Inhalation	No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate medical	attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide



# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 5 of 18 Print Date 07/18/2023

		carbon monoxide phosphorus oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containm	ent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the
		5/18

## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 6 of 18 Print Date 07/18/2023

same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Diundecyl phthalate	None.
Antimony trioxide	NIOSH REL (1994-06-01)





# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 7 of 18 Print Date 07/18/2023

		TWA 0.5 mg/m3 OSHA PEL 1989 (1989-03-01) TWA 0.5 mg/m3 (as Sb) OSHA PEL (1993-06-30) TWA 0.5 mg/m3 (as Sb) ACGIH TLV (2021-01-07) TWA 0.02 mg/m3 Form: Inhalable fraction
Proprietary Hazardous Compounds		None.
Carbon black		OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 0.1 mgPAH/m <sup>3</sup> ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to
Eye/face protection	:	remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be use

#### CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023



Page 8 of 18 Print Date 07/18/2023

higher degree of protection: chemical splash goggles. **Skin protection** Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Personal protective equipment for the body should be selected based **Body protection** : on the task being performed and the risks involved and should be approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures Other skin protection : should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. **Respiratory protection** Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state	:	liquid [liquid]
Color	:	BLACK
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
-		

# **ÄVIENT**

# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 9 of 18 Print Date 07/18/2023

Solubility Solubility in water Partition coefficient: n- octanol/water	:	Not available. Not available. Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.
<u>Aerosol product</u> Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Fl		Not available.
Flame duration	•	Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
Antimony oxide (Sb2O3)				
	LD50 Oral	Rat	34,000 mg/kg	-



## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023

#### Page 10 of 18 Print Date 07/18/2023

	LD50 Oral	Rat		15,400 m	g/kg	-
Conclusion/Summary	: Mix	cture.Not fully	v tested.			
Irritation/Corrosion						
Product/ingredient name	Result	Sp	ecies	Score	Exposure	e Observation
1,2-Benzenedicarboxylic acid, 1,2-diundecyl ester	Eyes - Mild irrit	tant Ra	bbit	-		-
Antimony oxide (Sb2O3)	Eyes - Mild irrit	tant Ra	bbit	-		-
Conclusion/Summary Skin Eyes Respiratory	: Mi	xture.Not full xture.Not full xture.Not full	y tested.			
Sensitization						
Conclusion/Summary Skin Respiratory		xture.Not full xture.Not full				
<u>Mutagenicity</u>						
Conclusion/Summary	: Mi	xture.Not full	y tested.			
<b>Carcinogenicity</b>						
Conclusion/Summary	: Mi	xture.Not full	y tested.			
<b>Classification</b>						
Product/ingredient name	OSHA	IARC	NTP			
Antimony oxide (Sb2O3) Carbon black	-	2A 2B	Reason	nably anticip	ated to be a	human carcinogen.
<u>Reproductive toxicity</u> Conclusion/Summary	: Mi	xture.Not full	y tested.			

**Teratogenicity** 

**Conclusion/Summary** : Mixture.Not fully tested.

#### Specific target organ toxicity (single exposure)

Not available.



# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 11 of 18 Print Date 07/18/2023

<u>Specific target organ toxicity (repeat</u> Not available.	ted e	<u>xposure)</u>
Aspiration hazard Not available.		
Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	:	Causes eye irritation. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards.
Symptoms related to the physical, ch	iemi	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: irritation, watering, redness
Inhalation	:	No specific data.
Skin contact	-	Adverse symptoms may include the following: irritation, redness
Ingestion	:	No specific data.
Delayed and immediate effects and a	also c	chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity Teratogenicity	:	No known significant effects or critical hazards. No known significant effects or critical hazards.



## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

:

:

:

Version Number 1.1 Revision Date 06/22/2023 Page 12 of 18 Print Date 07/18/2023

Developmental effects Fertility effects No known significant effects or critical hazards.

No known significant effects or critical hazards. No known significant effects or critical hazards.

Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
CORE™ DB5667 STATIC DISSIPATIV PVCBLK122	245424.6 mg/kg	N/A	N/A	N/A	N/A
Antimony oxide (Sb2O3)	34000 mg/kg	N/A	N/A	N/A	N/A
Proprietary Hazardous Compounds	500 mg/kg	N/A	N/A	N/A	N/A
Carbon black	15400 mg/kg	N/A	N/A	N/A	N/A

#### **Other information**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
1,2-Benzenedicarboxylic acid,	1,2-diundecyl ester		
	Acute EC50 12 Mg/l Fresh water	Daphnia - Daphnia magna	48 h
	Chronic NOEC 0.3 Mg/l Fresh	Fish - Oncorhynchus mykiss	155 d
	water		
	Chronic NOEC 0.059 Mg/l Fresh	Daphnia - Daphnia magna	21 d
	water		
Antimony oxide (Sb2O3)			
	Acute LC50 > 530 Mg/l Fresh	Fish - Lepomis macrochirus	96 h
	water		
	Acute EC50 560 Mg/l Fresh	Crustaceans - Cypris	48 h
	water	subglobosa	
	Acute EC50 3.01 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	10/10		

# **ÄVIENT**

# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023

#### Page 13 of 18 Print Date 07/18/2023

Carbon black				
	Acute EC water	C50 37.563 Mg/l Fresh	Daphnia - Daphnia magna	48 h
Conclusion/Summary	:	Not available.		
Persistence and degradability				
Conclusion/Summary	:	Not available.		
<b>Bioaccumulative potential</b> Not available.				
<u>Mobility in soil</u>				
Soil/water partition coefficien (KOC)	it :	Not available.		
Other adverse effects	:	No known significant	effects or critical hazards.	
Section 13. Disposa	l cons	iderations		
Disposal methods	:	possible. Disposal of t should at all times cor protection and waste of authority requirement products via a licensed disposed of untreated requirements of all au should be recycled. In	ste should be avoided or minimize this product, solutions and any by nply with the requirements of env disposal legislation and any region s. Dispose of surplus and non-rec d waste disposal contractor. Wast to the sewer unless fully complian thorities with jurisdiction. Waste ccineration or landfill should only feasible. This material and its cor	-products vironmental nal local yclable e should not be nt with the packaging be considered

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

and sewers.

disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains



# CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 14 of 18 Print Date 07/18/2023

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

# Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: The following components are listed: Alkanes, C14-17, chloro
		United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Listed Alkanes, C14-17, chloro
		United States - TSCA 5(a)2 - Proposed significant new use rules: Listed 4-Nonylphenol, branched
		United States - TSCA 5(e) - Substances consent order: Listed Alkanes, C14-17, chloro
		United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Listed Lead
		United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
		United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Poly(oxy-1,2-ethanediyl), .alpha(4- nonylphenyl)omegahydroxy-,branched (2-Methoxymethylethoxy)propanol 4-Nonylphenol, branched
		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed



## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 15 of 18 Print Date 07/18/2023

		United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Antimony trioxide 2-Ethylhexanoic acid zinc salt Phenol Arsenic Lead Vinyl chloride monomer
		United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Antimony trioxide	1309-64-4	1,000 lb(s)
		454 kg
Arsenic	7440-38-2	1 lb(s)
		0.454 kg

#### SARA 311/312

Classification

: EYE IRRITATION - Category 2B SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1B

**Composition/information on ingredients** 



## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 16 of 18 Print Date 07/18/2023

Name	%	Classification
1,2-Benzenedicarboxylic acid, 1,2-diundecyl ester	>= 25 - <= 50	EYE IRRITATION - Category 2B
Antimony oxide (Sb2O3)	>= 3 - <= 5	EYE IRRITATION - Category 2B CARCINOGENICITY - Category 1B
Proprietary Hazardous Compounds	>= 0.3 - < 1	FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY - oral - Category 4 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1A
Carbon black	> 0 - <= 0.3	CARCINOGENICITY - Category 2

#### <u>SARA 313</u>

#### Form R - Reporting requirements

Product name	CAS number	%
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omega	127087-87-0	>= 3 - < 7
hydroxy-,branched		
Antimony trioxide	1309-64-4	>= 1 - < 5
Lead	7439-92-1	>= 0 - < 0.1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: The following components are listed: Antimony trioxide
	Triphenyl phosphate
New York	: The following components are listed: Antimony trioxide
New Jersey	: The following components are listed:
-	Ethene, chloro-, homopolymer
	Alkanes, C14-17, chloro
	Antimony trioxide
	Triphenyl phosphate
	Carbon black
Pennsylvania	: The following components are listed:
	16/10

### CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number 1.1 Revision Date 06/22/2023 Page 17 of 18 Print Date 07/18/2023

Antimony trioxide

Triphenyl phosphate

#### California Prop. 65

**WARNING:** This product can expose you to chemicals including Antimony trioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Antimony trioxide	-	-
Carbon black	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	Not determined.
International regulations Inventory list		
Australia	:	Not determined.
Canada	:	Not determined.
China	:	Not determined.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
		Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

# Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4





## CORE™ DB5667 STATIC DISSIPATIV PVCBLK122

Version Number	er 1.1
<b>Revision Date</b>	06/22/2023

Page 18 of 18 Print Date 07/18/2023

representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<b>History</b>		
Date of printing	:	07/18/2023
Date of issue/Date of revision	:	06/22/2023
Date of previous issue	:	05/12/2022
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.